

**80 Shire Trail** Bozeman, MT. 59718 (406) 924-3535 (800) 940-0540

**QUOTE** 

**Paint Code** 

2959485000016433058

Contact **Seminole County Florida Jason Prather** jprather@seminolecountyfl.gov (407) 665-5188

**Louise Rainone Sales Person** 

**Quote Creation Date Quote Valid Until** 

Nov 22, 2022 04:22 PM

Jan 31, 2023 Estimated Delivery Date May 2023 TBD

Item & Description	List Price	Qty	Discount	Amount
6x6 Acela Monterra GL Chassis Cab (SWB)	\$ 119,950.00	2	0.0%	\$ 239,900.00
<b>GVWR 44,650 Lbs. (20,253 kg) Package - 6x6</b> Front GAWR: 13,000 lbs. (5,897 kg), Int. GAWR: 16,661 lbs. (7,557 kg), Rear GAWR: 16,661 lbs. (7,557 kg), GCWR: 65,650 lbs. (29,778 kg)	\$ 0.00	2	0.0%	\$ 0.00
High Speed Gearing (6x6 Models) Provides final gear ratio of 6.14:1 and top speed of 74MPH	\$ 9,990.00	2	0.0%	\$ 19,980.00
Deep Water Fording Kit (6x6) Increases water fording capabilities from 30 inches (762 mm) to 50 inches (1,168 mm) - 6x6 Chassis	\$ 2,662.00	2	0.0%	\$ 5,324.00
Safety-Style Cab Entry Steps Includes MSHA-compliant exterior entry steps	\$ 998.00	2	0.0%	\$ 1,996.00
Center Passenger Seat Includes standard center seat and seat belt. Air-ride seats not available for center seating position. Upgraded seating options available.	\$ 768.00	2	0.0%	\$ 1,536.00
Back-Up Alarm Includes 100db waterproof commercial back-up alarm (temporary- mounted for custom body placement).	\$ 153.00	2	0.0%	\$ 306.00
Back-Up Camera System  Includes infrared commercial back-up camera, 70-feet of cable, 6.2-inch monitor (temporary-mounted for custom body placement).	\$ 454.00	2	0.0%	\$ 908.00
Upfitter Auxiliary Dash Switch Pre-Wire Provides eight (8) backlit rubber push buttons on instrument panel, each programmable to On/Off or Momentary action. Remote 12VDC power module is pre-wired with three (3) fused 10A outputs and five (5) 0.2A outputs.	\$ 646.00	2	0.0%	\$ 1,292.00
Custom Exterior Paint Color Match cab paint color to customer specification.	\$ 813.00	2	0.0%	\$ 1,626.00
Tomar NFPA Warning Package - Silver NFPA-1901-compliant warning light/siren/chevron package, aluminum lightbar frame and chrome surface-mount light bezels (detailed list POR).	\$ 7,393.10	2	0.0%	\$ 14,786.20

Item & Description	List Price	Qty	Discount	Amount
PIAA Driving Lights Includes (2) PIAA LP550 5-3/16-Inch Round LED Driving Light Lamps, Mounted in Bumper. Requires Option 1047, Upfitter Auxiliary Switches	\$ 498.00	2	0.0%	\$ 996.00
NMO-Style 2-Way Radio Antenna Mount, Pre-Wired Includes NMO-style antenna base installed on cab roof, non-terminated RG58 cables run to dash area. Priced each.	\$ 169.00	2	0.0%	\$ 338.00
Front License Plate Bracket License plate bracket permanently mounted to front grille.	\$ 0.00	2	0.0%	\$ 0.00
Flood Rescue Body Package with Lift Gate 16-foot custom aluminum body, staircase, staircase rails bulkhead side uprights, folding aluminum seating, flush mount floor cargo tie-downs (98"W bed, 102" OAW bare smooth aluminum).	\$ 61,166.60	2	0.0%	\$ 122,333.20
Flood Rescue Sliding Canopy Sliding Canopy with bulkhead-mounted upward facing scene light, forward plastic window, side screen/velcro closure window.	\$ 4,895.00	2	0.0%	\$ 9,790.00
Flood Rescue Body Paint Paint body to customer specification	\$ 9,990.00	2	0.0%	\$ 19,980.00
Miscellaneous Includes front-mounted Sherpa 17,000 lb. winch with 6.6HP motor coupled with a 3-stage planetary gearbox. Winch has 90-feet of synthetic rope and aluminum hawse, wireless remote control, neoprene cover and 5-year manufacturer's warranty. Custom winch housing attaches to forward shackle mounting points.	\$ 7,500.00	2	0.0%	\$ 15,000.00
Shipping and Handling Shipping from Bozeman, MT. to Seminole County FL	\$ 9,200.00	2	0.0%	\$ 18,400.00
650- Gallon Slip In Unit 650 gallon tank 96 OAL x 54 OAL Manifold outlet 1" fire-type tank fill IPO industrial valve 1 1/2" Fire type ball valve service line with cap and chain Suction inlet Standard suction with two 2 1/2" fire grade ball valve Electric rewind hose reel 1" x 150' (ESF20-30-31-RT) Set of chrome outriggers w/ 3 way rollers 1" fabric booster hose (price per feet) Poly pre-connect hose tray to hold 1 3/4" x 200' 90 degrees 1 1/2" swivel	\$ 23,222.00	2	0.0%	\$ 46,444.00

 Sub Total
 \$ 520,935.40

 Discount
 \$ 18,232.74

Total \$ 502,702.66

NOTES: Includes a 3.5% Discount for 100% prepayment within 14 days of signing of sales agreement

**Terms & Conditions:** 

(800) 940-0540 I Acela Truck Company I www.acelatruck.com



### **6x6 HWFRT VEHICLE SPECIFICATIONS**

#### **Dimensional Data**

Width 96 in (2,438 mm)Height 112 in (2,845 mm) Pintle Height (Laden/Unladen) 33/36 in (838/905 mm) Length 270 in349 in (6,859 mm) Wheelbase 161 in 201 in (4,100 mm)(2,934 mm) Cab to Axle 1 115.5 in 163.1 in Turning Radius 56.4 f. (17.2 m)

**Ground Clearance** 

 Loaded
 22 in
 (559 mm)

 Under Axle
 14.4 in
 (365 mm)

Approach/Departure Angles\* 40° / 70°

Curb Weight (with Fuel)\* 18,446 lb (8,915 kg)

GVWR\* 30,750-49,000 lb (13,948-22,226 kg) Payload\* 12,304-30,000 lb (5,581-13,607 kg)

Maximum Towed Load 21,000 lb (9,526 kg)
Maximum Speed (Standard Gearing 58 MPH (93 km/h)

Maximum Speed (Optional High

 Speed Gearing)
 74 MPH
 (119 km/h)

 Fuel Tank
 58 gal
 (220 L)

Range (Optional Long-Range Fuel

Tanks Available) 400+ mi (645+ km)

Maximum Grade/Side Slope 60% / 30%

Water Fording Depth (Optional 50"

Fording Kit Available) 30 in (762 mm)

## **EQUIPMENT SPECIFICATIONS**

#### **Engine**

Caterpillar 3126/C7\*

6-Cylinder, 7.2 L, Electronically Controlled, Fuel-Injected,

Turbocharged and Aftercooled, EPA Certified

Rating 330 HP (246 kW) @ 2400 RPM

Displacement 441 cu in (7.2 L)

Torque 860 ft-lb (1,166 Nm) @ 1440 RPM

Fuel Type Diesel

Lubricant 15W40, Synthetic Blend

**Transmission** 

Allison MD 3700/3070SP Automatic, 7-speed, Electronically-Controlled, Power Take

Off

Full-Time AWD Integral Transfer Case

Normal Operations: 30% Front / 70% Rear Off-Road Mode:

50% Front / 50% Rear

Torque Split

Lubricant ATF, 31.8 gt (30 L

Axles, Meritor RF-611 Series

Front 13,000- 14,700 lb (5,897-6,668 kg) GAWR

Intermediate 8,875-18,000 lb (4,026-8,165 kg) GAWR

Rear 8,875-18,000 lb (4,026-8,165 kg) GAWR

Locker Automatic, Detroit Style, Intermediate Axle

Carrier Single Reduction, Amboid-Gearing Bevel

Wheel End Reduction, Ratio 2:1

Final Gear Ratio (Optional: 6.14:1

Available) Standard: 7.80:1

Front Axle Steering Angle 35°

Steering Power Assisted, Recirculating Ball, Adjustable Tilt Wheel

Suspension Parabolic-Tapered Leaf Springs with Hydraulic Twin-Tube

Shock Absorbers

**Brakes** 

Primary Dual-Circuit, Four Channel Air, Anti-Lock Braking System

Supplemental Air Actuated, Driver-Controlled Exhaust "Jake" Brake

Tires 46.6" Military Grade Tires

Spare Rack-Mounted, Hydraulic Lift

Central Tire Inflation System (CTIS), Dana/Eaton

General Cab-Mounted Electronic Controls, Operable While Driving in Highway,

Cross-Country, Sand/Mud/Snow, and Emergency Modes

Pressure Range 17-85 PSI (1.1-6.6 Bar)

**Electrical** 

Dual Voltage, 12/24VDC, Central

System Power Distribution Panel

Alternator 100 amp, 12/24 volt, Waterproof, EMI/RFI Suppressed

Starter 24 VDC, Waterproof

Batteries Dual 8D Commercial Batteries, CCA: 2700, CA 3380 880A Load

Instrumentation Can Bus-Driven Instrument Cluster

C/FMVSS Compliant, Ships with

Exterior Lighting Temp. Rear Lighting

Cab

Entertainment Extended Cab-Over Design

Commercial-Grade Trim Package,

Heavy-Duty Heat and Sound

General Insulation

AM/FM/DVD 6.2" Touchscreen

Trim Stereo

(2) 2.1A USB Power Ports, (1)

Seating 12VDC Cig. Style Plug

2-Person, Adjustable, High-Back, Air-Ride Seats (3-Person

Mechanical Access Optional)
Power Hydraulic Tilt

47,000 BTU/Hr (13.8 kw) Heating Capacity

HVAC 29,900 BTU/Hr (8.8 kw) Cooling Capacity

Airflow 334 SCFM 9.5 m /min

## 16-Foot High Water/Flood Rescue Body Specifications

- All aluminum custom high water/flood rescue body (192"L x 100"W)
- Integrated staircase with handrails and flip-down-style lower step
- OSHA-compliant safety gate at top of stairs
- LED lighted stepwell
- 46"H aluminum bulkhead and sidewalls
- Flip down seating (seats approximately 25 people)
- (4) Flush-mount heavy-duty cargo tie-downs in bed floor
- Non-skid Line-X bed liner applied to bed floor
- (1) Set, Q-Straint wheelchair tie-down anchors and straps, w/strap storage bags, instructional poster (\*additional wheelchair tie downs available)
- · Safety placards
- LED bed work lights
- LED rear scene/reverse lights
- LED marker/clearance/STT lighting
- Mudflaps and brackets
- Vertical exhaust stack, stainless steel and chrome
- Spare tire rack delete (Spare tire ships loose)
- 3000 lb. rail-style liftgate with dual controls, 54"D x 89"W Aluminum Platform
- NFPA green/red chevron pattern on stowed liftgate and rear bumper
- Sliding canopy
- 17,000 lb. front winch with custom mount

#### Standard Tomar NFPA Lighting Package

- Zone A Upper Tomar Scorpion LED Light Bar (Red/Blue/White) with Forward Flood Capability (Red/Blue Only when Park Brake Activated)
- Zone A Lower Tomar 4x6 LED Perimeter Light (Red/Blue)
- Zone B Upper Lightbar with Left/Right Scene Capability (Blue/White)
- Zone B Lower (2) Tomar 3x7 LED Perimeter Lights (Forward Corner Red/Blue, Rear Corner Red/Blue)
- Zone C Upper LED Rotating Beacon (1 Red, 1 Blue)
- Zone C Lower (2) Tomar 3x7 LED Perimeter Light (1 Red, 1 Blue)
- Zone D Upper Lightbar with Left/Right Scene Capability (Red/White)
- Zone D Lower (2) Tomar 3x7 LED Perimeter Lights (Forward Corner Red, Rear Corner Blue)

#### Siren

- Feniex Typhoon 100W Full-Featured Siren Controller with PA Capability
- Feniex Triton 100W Siren Speaker

#### 650-Gallon Slip in Unit

650-gallon Poly tank 96 OAL x 54 OAL Manifold outlet -1" fire type tank fill IPO industrial valve, 1 1/2" Fire type ball valve service line with cap and chain Standard suction with two 2 1/2" fire grade ball valve, Electric rewind hose reel 1" x 150' (ESF20-30-31-RT), Set of chrome outriggers x 3 way rollers, 1" fabric booster hose (price per feet), Poly pre-connect hose tray to hold 1 3/4" x 200'

90 degrees 1 1/2" swivel.

# HIGH WATER/ FLOOD RESCUE TRUCKS



50-INCH WATER FORDING CAPABILITY - 4X4 & 6X6 MODELS

Acela Truck Company, manufacturer of North America's most capable trucks, now offers purpose-built High Water/Flood Rescue Trucks in both 4x4 and 6x6 variations of it's Monterra<sup>TM</sup> line of truck chassis. With 47-inch tires, 23-inches of ground clearance, and a proprietary 50-inch water fording capability, there is no other modern truck platform that can compete when it comes to reliable and safe operations in flood waters. Available models and customizable configurations can safely transport up to 28 seated passengers (incl. driver) with ample room and payload for pets, personal property and rescue gear. Monterra flood rescue trucks can be used for virtually any disaster response such as tornadoes, hurricanes, blizzards, and earthquakes, easily traveling over or through large debris, sand and mud or double as brush/wildland fir e engines, Urban Search and Rescue (USAR) support vehicles, cargo haulers and SAR/SWAT team troop carriers, in any rural or urban environment. Monterras come standard with a bumper to bumper parts and labor warranty.





## Standard Flood Rescue Body

- · 16-foot Custom Aluminum Flood Rescue Body (97"W Bed, 101" OAW) (Bare Smooth Aluminum)
- · Integrated Staircase with Railing
- · Staircase Lower Flip-Style Step for Maximum Clearance
- · OSHA "Man bar" Safety Gate, Top of Stairs
- · Bulkhead and Side Walls
- · Folding Aluminum Seating, Full Perimeter
- · Non-Skid Bedliner Floor
- · (4) Flush-Mount Cargo Tie-Downs
- · WC tie-down strap w/storage bags (under seats), instructional poster on wall
- · Bed lighting, Lighted Stairs, Rear Scene/Reverse Lights
- 3000# Rail-Style Liftgate (bed-mounted pump) with dual controls
- LED DOT Marker/Clearance/Stop/Turn/Tail/Reverse Lighting
- · Safety Placards
- · Mudflaps
- · NFPA Rear Reflective Chevron Pattern

## Options

- · Paint
- Diesel-Fired Webasto Airtronics Heater for Passenger/Bed Area
- · Additional Flush-mount Wheelchair Tie-Downs in Bed Floor
- · Additional Scene Lighting

# Sliding Canopy Package

·Sliding canopy - 1 forward window and rear roll-down wall w/door and windows.





































































